



Technical

Specifications

OCP

PARAMETERS	METHOD	UNITS	TYPICAL VALUE
Appearance	-	-	White pellets
Density	ASTM D1505	kg/l	0,862
Polymer type	-	-	Semi-crystalline
K. viscosity 10% SN150/100c	ASTM D445	cSt	2524
Pour point 1% SN150 + 0,3% PPD21	ASTM D 97	°C	-12
Shear stability index	ASTM D6002	SSI	33,9
Ash content	ASTM D 1416	%	<0,1
Volatiles	ASTM D 1416	%	<0,1

Handling Health & Safety :

Lubricants consisting of highly refined mineral oils with specification additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.

İNOVATİF MAKİNA PETROL LOJİSTİK İTHALAT
İHRACAT SANAYİ VE TİCARET LİMİTED ŞİRKETİ
KÜME EVLERİ TRAK DEPOLARI NO : 444 İÇ KAP / NO 6 MERKEZ / EDİRNE
V.D : KIRKPINAR VKN : 663 094 0035



ASTM INTERNATIONAL