



Technical

Specifications

SN 150

PARAMETERS	METHOD	UNITS	GUARANTEED	TYPICAL
Kinematic viscosity at 100 °C	ASTM D 445	mm ² /s	5,2 - 5,9	5,52
Kinematic viscosity at 40 °C	ASTM D 445	mm ² /s	-	34,3
Viscosity index	ASTM D 227	-	Min 95	96
Density at 15 °C	ASTM D 4052-18 (A)	g/cm ³	-	0,864
Water content	ASTM D 6304-16e1 (A)	mg/kg	Max 100	12
Pour point	ASTM D 97	°C	Max -15	-15
Flash point	ASTM D 92	°C	Min 210	230
Acid number	ASTM D 664	mgKOH/g	Max 0,05	0,0154
Evaporation loss NOACK	DIN 51581	%(m/m)	Max 15	11
Appearance	Visual	-	Transparent, without any suspension	
Color	ASTM D 1500	-	Max 1,0	0,5

Handling Health & Safety :

Lubricants consisting of highly refined mineral oils with specification additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.

İNOVATİF MAKİNA PETROL LOJİSTİK İTHALAT
İHRACAT SANAYİ VE TİCARET LİMİTED ŞİRKETİ
KÜME EVLERİ TRAK DEPOLARI NO : 444 İÇ KAP / NO 6 MERKEZ / EDİRNE
V.D : KIRKPINAR VKN : 663 094 0035



ASTM INTERNATIONAL