



Technical

Specifications

4 cSt

PARAMETERS	TEST METHOD	UNITS	GUARANTEED	TYPICAL
Appearance	Visual	-	C&B	C&B
Color ASTM	ASTM D 1500	-	Max 0,5	L0,5
Kinematic viscosity at 50 °C	ASTM D 445	mm ² /s	-	14,12
Kinematic viscosity at 100 °C	ASTM D 445	mm ² /s	3,9 – 4,6	4,3
Viscosity index	ASTM D 2270	-	Min 125	130
Pour point	ASTM D 97	°C	Max -15	-18
Flash point OC	ASTM D 92	°C	Min 210	230
Sulfur	ASTM D 4294	ppm	Max 10	0,3
Density at 15°C	ASTM D 4052	kg/m ³	-	827
NOACK	ASM D 5800	wt%	Max 15	13

Handling Health & Safety :

Lubricants consisting of highly refined mineral oils with specification additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding can contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.

İNOVATİF MAKİNA PETROL LOJİSTİK İTHALAT
İHRACAT SANAYİ VE TİCARET LİMİTED ŞİRKETİ
KÜME EVLERİ TRAK DEPOLARI NO : 444 İÇ KAP / NO 6 MERKEZ / EDİRNE
V.D. : KIRKPINAR VKN : 663 094 0035



ASTM INTERNATIONAL